



creative sewing lab



BABY SHOES

• Sewing pattern & instructions •



MATERIAL LIST

- Fabric 1: 50cm x 30cm
- Fabric 2: 50cm x 40cm
- Volume Fleece H630 - Iron-on: 40cm x 20cm
- H250 - Standard Iron-on Interfacing: 40cm x 20cm
- Vliesofix/Bondaweb (double-sided iron-on adhesive interlining): 22cm x 10cm
- 30cm Velcro® tape
- tailor's chalk
- wooden picks for turning
- 20cm Stylefix (double-side adhesive tape)
- optional: anti-slip spray to make shoes slip-resistant

STEP 1: CUT FABRIC AND FLEECE TO LENGTH

First, cut all fabric and fleece pattern pieces to length using the pattern template. All template parts are titled exactly (fabric or fleece, number of pattern pieces required).

The soles are each cut to length 1x on fold, so that in each case you get two back-to-front accurately fitting pattern pieces.





Subsequently, trim the seam allowances all around it by 2mm.



Now, carefully turn the laces right-side out with the help of a rounded wooden pick and iron them.



Trim the laces at the open side by 2mm since the fabric frays here because of turning.

Cut the Velcro loop tape (Velcro®) into four even pieces. Per Velcro piece use the template and cut the Velcro loop tape accordingly.