

Jacke Segir

Raglan hooded jacket with
button panel and rolled up
sleeves



PiexSu

Table of contents

Adjust sewing pattern	4
Measurement table	5
Material	6
Consumption of fabric	6
Tools	6
Layers in PDF	7
Print the pattern.....	7
Gluing the pattern	8
Pattern pieces	8
Instructions	9
Sew raglan sleeves	9
Sew the hood.....	9
Sew side seams	10
Jacket parts compose	10
Sleeve hem sewing.....	11
Border or topstitch edges	12
Set buttons	12

The sewing patterns are in separate files.

ATTENTION!!!

If you have bought this pattern from Makerist, the page numbers may shift by one page because Makerist adds another page to the PDF.

It is best to use the instructions in the .zip file.

You will find the pattern in the .zip file in separate folders. For each fit class there is a folder with the pattern in A4 and A0.

Material

- Outer fabric: fleece, sweat or similar
- Lining: Jersey with at least 5% elastane
- 4 jersey press studs
- optional: cuffs or elastic binding tape



Consumption of fabric

in metres at 1,40 m (55,1 inch) width

Upper and lining fabric each

Size	56	62	68	74	80	86	92	98
Fabric cm (inch)	0,5 (0,20)	0,5 (0,20)	0,6 (0,24)	0,6 (0,24)	0,7 (0,28)	0,7 (0,28)	0,8 (0,32)	0,8 (0,32)

The amount of fabric can vary depending on pattern and seam allowance!

Tools

- Sewing machine and/or overlock machine
- Pins and/or fabric clamps
- Scissors
- Measuring tape
- Iron
- Trick marker or tailor's chalk
- Sewing Thread
- Iron and ironing board, possibly ironing aids

You can sew this pattern on any household sewing machine.

The pattern does **NOT** include a seam allowance!

So you have to **add a seam allowance** on all seams!

A seam allowance of 0.75 cm (0,3 inch) when sewing with the overlock sewing machine has proven to be well applicable.

Instructions

You can find the free video instructions for this pattern on my YouTube channel (german):

[see the video](#)

The snaps at the seams and at the divisions serve as an aid for sewing together, please transfer them all onto the fabric.

First cut all pieces with seam allowance from the fabric and transfer the markings in the side seam with a notch or tailor's chalk.



Sew raglan sleeves

Lay the back piece with the right side of the fabric facing you and position the sleeves right on the back piece.

Then sew them on with an overlock sewing machine or the elastic stitch of your normal sewing machine.



Now place the front pieces right sides together on the sleeves and sew them on with an overlock sewing machine or the elastic stitch of your normal sewing machine.



Sew the hood

Place one hood piece of the lining fabric on each of the second cut pieces and sew them together along the curve.