

# FROM THE FOUNDER OF THE #VIKISEWS BRAND

---



Back in 2016, when I was working on my first set of sewing instructions, I was trying to write them in such a way that even a complete beginner could easily understand and use them to create their very first garment. These instructions laid the foundation for the Vikisews brand, its vision and its mission. I wanted to create modern patterns with the utmost detailed and clear instructions.

Now, with each new collection we are constantly improving our instructions, amending them and adding more relevant details. By the time the final product reaches you, our drafters, correctors, and editors would have spent weeks perfecting every word and every photograph. If you compile a few of our instructions together, you will get a sewing manual that will assist you in sewing all kinds of garments at any difficulty level.

And I would be very happy if these instructions helped you to turn your hobby into a lifelong passion... Enjoy the process! Create your ultimate dream wardrobe! Wear your garments proudly for years to come!

If you have any questions, please contact us at [info@vikisews.com](mailto:info@vikisews.com) — we are always there to help.



## SORELLE PATTERN DESCRIPTION

---

Sorelle is a pair of lined, semi-fitted, A-line shorts. The back features waist darts. There are pockets in the side seams. Sorelle fastens with an invisible zipper in the center back seam. The waistband has a hook-and-eye closure. The scalloped hem is finished with lace trim. Sorelle shorts are above mid-hip length.



## IMPORTANT!

---

The contents of this pattern are copyright protected and belong exclusively to Vikisews. You may use Vikisews patterns for personal use. It is prohibited to share Vikisews patterns and instructions with third parties, as well as to publish patterns and instructions online for public access. According to part 1 of clause 1252 and clause 1301 of the Civil Code of the Russian Federation, failure to comply with the mentioned rules constitutes a breach of the legislation in force in the field of copyright and entails liability of the violator. Illegal use or distribution will be prosecuted in accordance with legislation.

You may use Vikisews patterns for commercial use, to sew custom-made garments and/or create fashion collections, on the condition that the patterns are solely used in a manufacturing setting and are not further shared with individuals.

# TOTAL EASE ALLOWANCE

---

	Waistline ease	Hipline ease
cm	3.9–6.4	12.2–16.2
inches	1 1/2–2 1/2	4 3/4–6 3/8

# GARMENT LENGTH

---

Height, cm	Side seam length including waistband, cm
1 (154–160)	35.4–36.9
2 (162–168)	36.4–37.8
3 (170–176)	38.4–39.8
4 (178–184)	40.4–41.8

Height, ft	Side seam length including waistband, in
1 (5'1"–5'3")	13 7/8–14 1/2
2 (5'4"–5'6")	14 3/8–14 7/8
3 (5'7"–5'9")	15 1/8–15 5/8
4 (5'10"–6'1")	15 7/8–16 1/2

3. Lace trim for the hem finishing, 1–1.5 cm wide, in meters:

Height, cm	Sizes									
	34	36	38	40	42	44	46	48	50	52
1 (154–160)	1.68	1.73	1.78	1.83	1.88	1.93	1.99	2.04	2.09	2.14
2 (162–168)	1.69	1.74	1.79	1.84	1.89	1.94	2	2.05	2.10	2.15
3 (170–176)	1.72	1.77	1.82	1.87	1.92	1.96	2.02	2.06	2.11	2.16
4 (178–184)	1.72	1.77	1.82	1.87	1.92	1.97	2.02	2.07	2.12	2.18

Lace trim for the hem finishing, 3/8–5/8" wide, in yards:

Height, ft	Sizes									
	34	36	38	40	42	44	46	48	50	52
1 (5'1"–5'3")	1 7/8	1 7/8	2	2	2	2 1/8	2 1/8	2 1/4	2 1/4	2 3/8
2 (5'4"–5'6")	1 7/8	1 7/8	2	2	2 1/8	2 1/8	2 1/8	2 1/4	2 1/4	2 3/8
3 (5'7"–5'9")	1 7/8	1 7/8	2	2	2 1/8	2 1/8	2 1/4	2 1/4	2 1/4	2 3/8
4 (5'10"–6'1")	1 7/8	1 7/8	2	2	2 1/8	2 1/8	2 1/4	2 1/4	2 3/8	2 3/8

4. One pair of trouser hook-and-eye fastener.

5. Stitched straight fusible stay tape, 1 cm (3/8") wide — 0.6 m (5/8 yd).

6. Stitched fusible stay tape with stitch reinforcement, 1.5 cm (5/8") wide — 0.5 m (1/2 yd).

7. One 25 cm (9 7/8") long invisible zipper.

8. Matching thread — 5 spools (1 spool for the sewing machine + 4 spools for the overlocker).



Pin the dart on the wrong side of the back leg piece.



Machine-stitch the dart, backstitching at the top edge only. Tie the thread tails at the dart point into a knot and hide them inside the dart bulk using a needle.



Press the dart seam flat.